

# GaN Microwave Amplifier RIK138K0-40T



## Product Features

- 1299 ~ 1301MHz
- High Output Power : 8kW(CW)
- Using GaN on SiC HEMT
- 58% System Efficiency
- High Reliability & Stability, Long-run Operation
- Stable frequency spectrum even at low power

## Applications

- Building block for high-power systems
- Accelerator Light Source
- Industrial Heating and Drying
- Microwave CVD
- Materials processing
- Study of biological phenomena
- Food sterilization / pasteurization

## Description

The RIK138K0-40T is a high-power microwave generator (SSPA) utilizing cutting-edge GaN on SiC HEMT technology, delivering high breakdown voltage and exceptional power efficiency. This product is engineered to meet the stringent and precise requirements of modern particle accelerators and synchrotron light sources.

## Electrical Specifications

PARAMETER		UNIT	MIN	TYP	MAX
Operating Frequency		MHz	1299	-	1301
Operating Bandwidth		MHz	-	2	-
CW Output Power		W	100	-	8000
System Efficiency		%	58	-	-
Input Power		dBm	-3	-	3
In/Out Return Loss		dB	-	-	-15
Operating Case Temperature		°C	-	-	60
Rise and fall time in pulse operation		us		≤ 10	
2 <sup>nd</sup> harmonic		dBc		≤ -42	
3 <sup>rd</sup> harmonic		dBc		≤ -59	
Spurious and sideband		dBc		≤ -60	
Phase noise 10Hz-300Hz		dBc		< -60	
Phase noise > 300Hz		dBc		< -80	
Monitoring	FWD & RVS Power	System Output and Reflect Power from 10 to 100%			
	Temperature	Individual Power Amplifier			
	Current	+50Vdc Output of Power Supply Unit			
Maximum mismatch for full power output		6 : 1 VSWR 30sec.			
Phase Shift	Operating Range	Deg	0	-	360
	Step Size	Deg	-	5.6	-

### Generator Alarm & Protection Features

PARAMETER	State	CONDITION
Output Power	Alarm	Output Power > 8.2kW
Over-Temperature	Alarm	System Temperature > 50° C
Reflected Power	Alarm	Reflected Power > Output Power*0.5
Over input Power	Disabled	+3dBm
Over Water Temperature	Disabled	>33° C
Low Water Flow	Disabled	<16L/M
Over-Temperature	Disabled	System Temperature > 55° C
Reflected Power	Disabled	Reflected Power > 4kW


### Environmental Conditions

PARAMETER	Value	note
Supply voltage	380Vac 3 phase 4wire 50/60Hz	
Input Current	3 x 19.4A	8kW (CW)
Power factor	≥ 0.9	
Ambient temperature	15 – 35°C	
Humidity	20 – 65%	
Output Voltage	50Vdc	
PSU Cooling	Air Cooling	

## Mechanical Specifications

PARAMETER	UNIT	VALUE
Dimensions (W x D x H)	mm	600 x 1100 x 978
Weight	kg	200
Microwave Input Port	-	N-type
Microwave Output Port	-	WR650
Input,Output Monitoring Port	-	N-type
VAC & GND	-	380 VAC 3 phase 4wire 50/60 Hz & R,S,T,N,GND(Y Connection)
Control Interface		EPICS, Ethernet
Cooling Requirements		<b>Water Cooling Rate</b> 20L/Min, 6~8Bar
		<b>Cooling Water Inlet Temperature</b> 29 °C~31°C (typ.)
		Relative humidity below dew point (non-condensing)
		* De-ionized water shall be used to prevent system damage
Fluid Inlet Size	Inch	1/2" male
Fluid Outlet Size	Inch	1/2" male

Dimension and weight may be subject to change.



# GaN Microwave Amplifier RIK138K0-40T



## Revision History

Part Number	Release Date	Version	Description	Data Sheet Status
RIK138K0-40T	JUN, 2026	0.1	Initial release of datasheet	



### Certification

This product is manufactured by a company that is certified for the AS9100D quality management system.

RFHIC Corporation reserves the right to make changes to any products herein or to discontinue any product at any time without notice. While product specifications have been thoroughly examined for reliability, RFHIC Corporation strongly recommends buyers to verify that the information they are using is accurate before ordering. RFHIC Corporation does not assume any liability for the suitability of its products for any particular purpose, and disclaims any and all liability, including without limitation consequential or incidental damages. RFHIC products are not intended for use in life support equipment or application where malfunction of the product can be expected to result in personal injury or death. Buyer uses or sells such products for any such unintended or unauthorized application, buyer shall indemnify, protect, and hold RFHIC Corporation and its directors, officers, stockholders, employees, representatives and distributors harmless against any and all claims arising out of such unauthorized use. All sales inquiries and support should be directed to the local authorized geographic distributor for RFHIC Corporation. For customers in the US, please contact the US sales team through our website at <https://rfhic.com/rfhic-us/>. For all other inquiries, please contact our international sales team through our website portal at <https://rfhic.com/contact/>